

T1000 UNITS


TECHNICAL DATASHEET

The patented WCSEE Hybrid™ precision engineered modular treatment system delivers more efficient processing than a traditional Submerged Aerated Filter (SAF). The above ground modular T1000 vessels are manufactured in steel in a quality controlled environment.



KEY FEATURES:

- High-rate process (submerged moving-bed, fixed-film reactor)
- Capable of achieving low ammonia effluent quality
- Site footprint requirement 30% smaller (comparable technologies)
- Energy consumption reduced in line with footprint reduction
- Off-site build significantly reduces installation time
- Scalable to accommodate growing populations
- No mechanical or electrical moving parts within the cells
- Can be redeployed if the asset becomes redundant before end-of-life



TECHNICAL TABLE:

Model	Length (mm)	Width (mm)	Height (mm)	Length w/ handr (mm)	Width w/ handr (mm)	Height w/ handr (mm)	In/Outlet Size	Inlet Invert (mm)	Outlet Invert (mm)	Media Rentention (m³)	Dry Weight (TE)	Operating Weight (TE)	Dry Weight After Oper (TE)	Available for hire
	(A)	(B)	(C)	(A)	(B)	(C)								
T1000	9125	2438	2996	10100	2438	4000	8"	520	660	29	16	63	22	✓

Disclaimer

WCS Environmental Engineering has a policy of continual product development and the above information may be subject to change without notice. Errors and omissions excepted. Technical drawings are indicative only. WCS Environmental Engineering Ltd is a portfolio company of Marlowe PLC. Updated September 2024