## **DIAMOND LOGBOOK**

Service and maintenance log book (English Language)





# **TABLE OF CONTENTS**

Servicing and maintenance	3
Diamond plant identification	4
Plant inspection record	5
Desludge record	15
Authorised parts fitting record	25

## **SERVICING AND MAINTENENCE**

#### SERVICING AND MAINTENANCE

The owner is responsible for the Diamond plant (formerly WPL Diamond), ensuring that the effluent quality does not breach applicable discharge consent standards. Please visit your local Environment Agency website for guidance. The plant requires routine, periodic inspection and maintenance to ensure continuous, trouble-free operation. WCSEE recommends service and maintenance to be undertaken by a British Water Accredited service engineer. All service and maintenance for the plant must be recorded in this logbook which should be retained by the owner for the lifetime of the plant.

The logbook can be downloaded from wpldiamond website / support / useful documents.

The Diamond is CE marked, fully type tested and certificated in accordance with the mandatory European standard BS EN12566-3, and meets all current legislation under the Environmental Permitting Programme.

#### WARRANTY AND RECORD

Please keep a record of your servicing and maintenance in line with the warranty. The Diamond comes with 25 years tank warranty and a process performance guarantee for the life of the tank.

The warranty of the air blower (housed in the kiosk) is 2 years. Warranty is subject to the correct installation, consistent influent conditions and regular plant maintenance as per the manufacturers' instructions.

#### **Tank inspection**

At a minimum, the tank should be inspected every six months. More frequent inspections may be required if mandated by local or national regulatory authorities, or if the tank is used in a non-residential application.

#### **Blower inspection**

Please refer to the specific instruction manual supplied with the air blower. Warranty is subject to the manufacturer's instructions.

#### **De-sludging**

This should be carried out by professionals holding the relevant permits to transport and dispose of sewage sludge. They will also be able to advise the correct de-sludge frequency by analysing the percentage of settled sludge (i.e. sludge volume) to the clear liquor.

FOR MORE INFORMATION ON THE SERVICE AND MAINTENANCE, PLEASE REFER TO THE DIAMOND MANUAL.

AUTHORISED SERVICE KITS AND SPARE PARTS ARE SUPPLIED BY WPL OR CONTACT YOUR LOCAL PROVIDER.

ADDITIONAL PAGES FOR PLANT INSPECTION, DESLUDGE OR AUTHORISED PARTS FITTING RECORDS CAN BE DOWNLOAD AT:

wcs-group.co.uk/accreditations-repository

## **DIAMOND PLANT INDENTIFICATION**

Address (where the	plant is located	)						
Diamond seria (located under the tank	al numbei	r						
	DMS2	DMS 3	DMS 4	DMS 5	DMS 6	DMS 7	DMS 8	DMS 9
Model	1-6	5-11	10-15	14-20	21-27	28-35	36-45	46-55
Standard								
With EPC*								
*External pumping ch	namber							
Purchase Date	e						<u>.</u>	
Installation Da	ate							
Commisioning	g Date							
(Operation start-up date								
COMPANY IN:	STALLING	G / COMIS	SSIONING	THE PLA	ANT			
Company stamp an	d signature							

## **PLANT INSPECTION RECORD**

The plant inspection list is a guide designed to ensure the treatment system is properly maintained throughout its life. Please tick each box once the item has been completed. Comments on unusual condition and subsequent remedial action taken must be added.

AIR BLOWER & KIOSK	
Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
). Odour	OUTLET
. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
B. Remove rags/fat	23. Sample colour/clarity
Please document any unusual conditions observed and any	/ remedial actions taken
ervice company contract number	

Date checked	
AIR BLOWER & KIOSK	
1 Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
10. Odour	OUTLET
11. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
12. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
13. Remove rags/fat	23. Sample colour/clarity
Please document any unusual conditions observed and any	remedial actions taken.
Service company contract number	
Company stamp and signature	

Date checked		
AIR BLOWER & KIOSK	14. Remove rags/fat	
1 Air Blower noise (lid on/off)	15. Air distribution pipework	
2. Air blower temp (37-40oC max)	16. Air diffuser condition	
3. Check oil level (DMC blowers only)	17. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)	
4. Renew blower diaphragms	CLARIFYING CHAMBER	
5. Air filter condition/cleanliness	18. Move scum to aeration chamber	
6. Kiosk secure/dry/clean	EXTERNAL PUMP CHAMBER (if fitted)	
7. Kiosk venting	19. Clean pump chamber	
8. Hose connection/condition	20. Check operation of pump	
9. Electrical connections	21. Check non-return valve works	
AERATION CHAMBER	22. Check high level float & beacon	
10. Plant lid secure	OUTLET	
11. Odour	23. Outlet 'T' correctly orientated & obstruction free	
12. Aeration turbulence	SAMPLE CHAMBER (if fitted)	
13. Liquor colour (brown)	24. Sample colour/clarity	
Please document any unusual conditions observed and any	remedial actions taken	
Service company contract number		
Company stamp and signature		

Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
). Odour	OUTLET
. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
2. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
3. Remove rags/fat	23. Sample colour/clarity
Please document any unusual conditions observed and	d any remedial actions taken
ervice company contract number	

AIR BLOWER & KIOSK	
1 Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
10. Odour	OUTLET
11. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
12. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
13. Remove rags/fat	23. Sample colour/clarity
Please document any unusual conditions observed and	
ervice company contract number	
ervice company contract number	
ervice company contract number	

Date checked	
AIR BLOWER & KIOSK	14. Remove rags/fat
1 Air Blower noise (lid on/off)	15. Air distribution pipework
2. Air blower temp (37-40oC max)	16. Air diffuser condition
3. Check oil level (DMC blowers only)	17. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Renew blower diaphragms	CLARIFYING CHAMBER
5. Air filter condition/cleanliness	18. Move scum to aeration chamber
6. Kiosk secure/dry/clean	EXTERNAL PUMP CHAMBER (if fitted)
7. Kiosk venting	19. Clean pump chamber
8. Hose connection/condition	20. Check operation of pump
9. Electrical connections	21. Check non-return valve works
AERATION CHAMBER	22. Check high level float & beacon
10. Plant lid secure	OUTLET
11. Odour	23. Outlet 'T' correctly orientated & obstruction free
12. Aeration turbulence	SAMPLE CHAMBER (if fitted)
13. Liquor colour (brown)	24. Sample colour/clarity
Please document any unusual conditions observed and any	remedial actions taken
Service company contract number	
Company stamp and signature	

Date checked		
AIR BLOWER & KIOSK		
1 Air Blower noise (lid on/off)	14. Air distribution pipework	
2. Air blower temp (37-40oC max)	15. Air diffuser condition	
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)	
4. Air filter condition/cleanliness	CLARIFYING CHAMBER	
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber	
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)	
7. Hose connection/condition	18. Clean pump chamber	
8. Electrical connections	19. Check operation of pump	
AERATION CHAMBER	20. Check non-return valve works	
9. Plant lid secure	21. Check high level float & beacon	
10. Odour	OUTLET	
11. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free	
12. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)	
13. Remove rags/fat	23. Sample colour/clarity	
Please document any unusual conditions observed and	any remedial actions taken	
Company stamp and signature		

AIR BLOWER & KIOSK	
1. Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
0. Odour	OUTLET
1. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
2. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
3. Remove rags/fat	23. Sample colour/clarity
Please document any unusual conditions observed and a	ny remedial actions taken
ervice company contract number	

Date checked	
AIR BLOWER & KIOSK	14. Remove rags/fat
1 Air Blower noise (lid on/off)	15. Air distribution pipework
2. Air blower temp (37-40oC max)	16. Air diffuser condition
3. Check oil level (DMC blowers only)	17. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Renew blower diaphragms	CLARIFYING CHAMBER
5. Air filter condition/cleanliness	18. Move scum to aeration chamber
6. Kiosk secure/dry/clean	EXTERNAL PUMP CHAMBER (if fitted)
7. Kiosk venting	19. Clean pump chamber
8. Hose connection/condition	20. Check operation of pump
9. Electrical connections	21. Check non-return valve works
AERATION CHAMBER	22. Check high level float & beacon
10. Plant lid secure	OUTLET
11. Odour	23. Outlet 'T' correctly orientated & obstruction free
12. Aeration turbulence	SAMPLE CHAMBER (if fitted)
13. Liquor colour (brown)	24. Sample colour/clarity
Please document any unusual conditions observed and any	remedial actions taken
Service company contract number	
Company stamp and signature	

AIR BLOWER & KIOSK	
1 Air Blower noise (lid on/off)	14. Air distribution pipework
2. Air blower temp (37-40oC max)	15. Air diffuser condition
3. Check oil level (DMC blowers only)	16. Settlement test below 70% sludge (Mixed Liquors Suspended Solids)
4. Air filter condition/cleanliness	CLARIFYING CHAMBER
5. Kiosk secure/dry/clean	17. Move scum to aeration chamber
6. Kiosk venting	EXTERNAL PUMP CHAMBER (if fitted)
7. Hose connection/condition	18. Clean pump chamber
8. Electrical connections	19. Check operation of pump
AERATION CHAMBER	20. Check non-return valve works
9. Plant lid secure	21. Check high level float & beacon
.O. Odour	OUTLET
1. Aeration turbulence	22. Outlet 'T' correctly orientated & obstruction free
2. Liquor colour (brown)	SAMPLE CHAMBER (if fitted)
.3. Remove rags/fat	23. Sample colour/clarity
ervice company contract number	,
ervice company contract number  Company stamp and signature	

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature
DESLUDGE RECORD  Date of desludge
Comments on unusual condition and subsequent remedial action taken:
Service company contract number
Company stamp and signature

## **AUTHORISED PARTS FITTING RECORD**

## PARTS RECORD

Part description
Part number  Date fitted
Service company contract number
Company stamp and signature
Part description
Part number
Date fitted
Service company contract number
Company stamp and signature

## PARTS RECORD

Part description
Part number Date fitted
Service company contract number
Company stamp and signature
PARTS RECORD
Part description
Part number
Date fitted
Service company contract number
Company stamp and signature

## PARTS RECORD

Part description
Part number Date fitted
Service company contract number
Company stamp and signature
PARTS RECORD
Part description
Part number
Date fitted
Service company contract number
Company stamp and signature

## **OUR ROOTS**

WPL (which is now a part of WCS Environmental Engineering) has been at the forefront of wastewater treatment technology for over 30 years, with international experience of technical design, quality of manufacture and supply of environmental wastewater solutions. Our high level of expertise means that we offer all of our customers, from the individual homeowner to large municipal communities and industrial markets, robust wastewater treatment process solutions that are environmentally compliant.

WCS Environmental Engineering Ltd Unit 1 Aston Road Waterlooville Hampshire PO7 7UX United Kingdom Tel: +44 (0)23 9224 2600 Email: info@wcs-group.co.uk Web: wcs-group.co.uk/

environmental-engineering-diamond

#### **Disclaimer**

WCS Environmental Engineering has a policy of continual product development and the above information may be subject to change without notice. Errors and omissions excepted. Technical drawings are indicative only. WCS Environmental Engineering Ltd is a portfolio company of Marlowe PLC.